















# "LENOX" SAW BLADES - USA

## NO. S 85-12 "LENOX" BI-METAL JIG SAW BLADE FOR BOSCH TYPE (T-SHANK)

BOSCH TYPE SHANK  : Fits DEWALT, BOSCH, B&D, MAKITA and HITACHI Jig Saws, using BOSCH type shank.

Item No.	Lgth x TPI Thickness x Width	Milled or Ground	Application	Price (set)	
 <b>450S</b>	<b>085-12-450S</b>	4" x 10T 1.5 mm x 8mm	Ground	Ground teeth for fast, smooth cuts in wood, plastic and composition material: 5-38mm thick.	(set of 5pcs)
 <b>B318T3</b>	<b>085-12-B318T3</b>	3-5/8" x 18T 0.9mm x 9.5mm	Milled	Medium metal: 1.6 to 6.4mm thick.	(set of 3pcs)
 <b>B324T3</b>	<b>085-12-B324T3</b>	3-5/8" x 24T 0.9mm x 9.5mm	Milled	Thin metal: Up to 3.2mm thick.	
 <b>B332T3</b>	<b>085-12-B332T3</b>	3-5/8" x 32T 0.9mm x 10mm	Milled	Thin stainless steel, sheet metal: Up to 1.6mm. Non-ferrous metal: Up to 3.2mm thick.	
 <b>B514T3</b>	<b>085-12-B514T3</b>	5-1/4" x 14T 0.9mm x 9.5mm	Milled	Metal: Greater than 2.4mm thick. Pipe: Up to 76.2mm thick.	
 <b>B524T3</b>	<b>085-12-B524T3</b>	5-1/4" x 24T 0.9mm x 9.5mm	Milled	Thin metal: Up to 3.2mm thick. Pipe: Up to 63.5mm thick.	
 <b>B680T3</b>	<b>085-12-B680T3</b>	5-1/4" x 10T 1.3mm x 9.5mm	Milled	Thick, wide teeth durable to cut metal and nail embedded wood.	(set of 2pcs)
 <b>* BT314S</b>	<b>085-12-BT314S</b>	3-5/8" x 14T 0.9mm x 10mm	Milled	Steels: 2.5-6mm. Non-ferrous metal: 2.5-10mm.	
 <b>BT320SC</b>	<b>085-12-BT320SC</b>	3-1/4" x 20T 1.5mm x 5mm	Ground	Ground teeth for fine contour cutting in wood, veneer, laminate and plastic: 1.5-13mm.	
 <b>BT332S</b>	<b>085-12-BT332S</b>	3-5/8" x 32T 0.9mm x 10mm	Milled	Thin stainless steel, sheet metal: Up to 1.6mm. Non-ferrous metal: Up to 3.2mm thick.	
 <b>BT406S</b>	<b>085-12-BT406S</b>	4" x 6T 1.3mm x 10mm	Milled	Fast, rough cutting in wood and composition material: 10-50mm thick.	
 <b>*BT410S</b>	<b>085-12-BT410S</b>	4" x 10T 1.3mm x 10mm	Milled	Woods: 6-50mm thick. All steels: 3.2-13mm. Soft metals: 3.2-25mm.	(set of 3pcs)
 <b>G300T3</b>	<b>085-12-G300T3</b>	3-1/2" 0.8mm x 8mm	Medium Carbide Grit	Cast iron, fibreglass, ceramic tile, hard plaster.	

\* Tuff Tooth™