

"LENOX" CARBIDE TIPPED HOLE SAWS - USA

NO. S 85-17 "LENOX" CARBIDE TIPPED HOLE SAW

Newly designed carbide tipped hole saws with greater wear and heat resistance than bi-metal hole saws. Cutting depth is 38mm (1-1/2"). Suitable for cutting plastics, fiber-glass, ceramic tile, cast iron and stainless steel.

Carbide Tipped Hole Saws use standard arbors. However, we recommend the use of a carbide tipped pilot drill (123CT) when using a carbide tipped hole saw cutting ceramic wall tiles.



Item No.	Diameter		Use Arbor Number	Price (pc)
	Inch	(mm)		
085-17-C017	11/16	(17)	1L, 4L	
085-17-C019	3/4	(19)	1L, 4L	
085-17-C022	7/8	(22)	1L, 4L	
085-17-C025	1	(25)	1L, 4L	
085-17-C029	1-1/8	(29)	1L, 4L	
085-17-C032	1-1/4	(32)	2L	
085-17-C035	1-3/8	(35)	2L	
085-17-C038	1-1/2	(38)	2L, 7L	
085-17-C041	1-5/8	(41)	2L, 7L	
085-17-C044	1-3/4	(44)	2L, 7L	
085-17-C051	2	(51)	2L, 7L	
085-17-C054	2-1/8	(54)	2L, 7L	
085-17-C057	2-1/4	(57)	2L, 7L	
085-17-C060	2-3/8	(60)	2L, 7L	
085-17-C064	2-1/2	(64)	2L, 7L	
085-17-C065	2-9/16	(65)	2L, 7L	
085-17-C067	2-5/8	(67)	2L, 7L	
085-17-C068	2-11/16	(68)	2L, 7L	
085-17-C076	3	(76)	2L, 7L	
085-17-C083	3-1/4	(83)	2L, 7L	
085-17-C086	3-3/8	(86)	2L, 7L	
085-17-C089	3-1/2	(89)	2L, 7L	
085-17-C092	3-5/8	(92)	2L, 7L	
085-17-C095	3-3/4	(95)	2L, 7L	
085-17-C102	4	(102)	2L, 7L	
085-17-C105	4-1/8	(105)	2L, 7L	
085-17-C108	4-1/4	(108)	2L, 7L	
085-17-C114	4-1/2	(114)	2L, 7L	
085-17-C121	4-3/4	(121)	2L, 7L	
085-17-C127	5	(127)	2L, 7L	
085-17-C140	5-1/2	(140)	2L, 7L	
085-17-C152	6	(152)	2L, 7L	
085-17-SD	123CT Carbide Tipped Pilot Drill (Fits Arbor No. 1L, 2L, 4L, 7L)			

Packing: Hole Saw - 1 pc/box
123CT Drill - 1 pc/pack