

"DEWALT" POWER TOOL - USA

NO. S 161-8 DEWALT 20V MAX BRUSHLESS 1/2" HOG RING IMPACT WRENCH - DCF900N (BARE) - DCF900P2T (5.0AH x 2) - Self Assembly



DCF900N



DCF900P2T

High Torque Impact Wrench. Delivering 1030 ft-lbs. of max fastening torque and 1400 ft-lbs. of max breakaway torque, it is ideal for large pipe flanges, grooved couplings, wheel lugs, concrete anchor bolt setting, and other heavy-duty impact wrench applications.

| Item No. | Description | Weight (without Battery) | Price (set) |
|------------------|--|-----------------------------|----------------|
| 161-08-DCF900N | 20V Max Brushless 1/2" Hog Ring Impact Wrench (Bare) <u>Technical Specifications</u> Voltage : 20V Max (18V) Battery Type : Lithium-Ion No-Load Speed : 0-2300 rpm Impact Rate : 0-2200 ipm Max Tightening Torque : 1396 Nm Max Breakaway Torque : 1898 Nm Tool Holder : 12.7 mm (1/2") *** Batteries and Chargers NOT included *** | 2.9 kgs | |
| 161-09-DCF900P2T | 20V Max Brushless 1/2" Hog Ring Impact Wrench (5.0Ah x 2) <u>Technical Specifications : Same as above</u> <u>Included</u> : 2 x 5.0Ah (DCB184) Battery, 1pc DCB1104 Charger, DSWT17807 TSTAK Carrying Case. | 2.9 kgs | |

NO. S 161-9 / 9X DEWALT 20V MAX XR®BRUSHLESS 1/2" HOG RING 1626NM IMPACT WRENCH IN TSTAK - DCF961NT (BARE) - DCF961P2T (5.0AH x 2) - Self Assembly



DCF961NT



DCF961P2T

Complete tough jobs utilizing the power of the 20V XR 1/2" High Torque Impact Wrench. Delivering 1,626 Nm of torque and 2,372 Nm of breakaway torque, up to 71% more than DCF899, making it ideal for heavy-duty fastening applications. After 4 seconds of impacting, the tool automatically provides an increase in power to aid in loosening stubborn fasteners.

| Item No. | Description | Weight (without Battery) | Price (set) |
|-------------------|--|-----------------------------|--|
| 161-09-DCF961NT | 20V Max XR® Brushless 1/2" Hog Ring 1626Nm Impact Wrench (Bare) <u>Technical Specifications</u> Voltage : 20V Max (18V) Battery Type : Lithium-Ion Anvil Size and Type : 12.7mm(1/2") Hog Ring Anvil No-Load Speed : 0-1200 rpm Impact Rate : 1890 ipm Max Tightening Torque : 1626 Nm Max Breakaway Torque : 2372 Nm *** Batteries and Chargers NOT included *** | 3.5 kgs | <u>Included</u> Carrying Case (TSTAK) LED Light : Yes Brushless : Yes Motor |
| 161-09X-DCF961P2T | 20V Max XR® Brushless 1/2" Hog Ring 1626Nm Impact Wrench <u>Technical Specifications : Same as above</u> <u>Included</u> : 2 x 5.0Ah (DCB184) Battery, 1pc DCB1104 Charger, DSWT17807 TSTAK Carrying Case. | 3.5 kgs | |